

MIRAGE-P510D

Dual-channel TMS320 DSP Emulator for PCI-bus Computers

User's Guide

covers:
MP510D rev.1B

MicroLAB Systems Ltd

59a Beskudnikovskiy blvd, 127486, Moscow, RUSSIA

phone/fax: +7-(095)-485-6332 E-mail: info@mlabsys.com WWW: <http://www.mlabsys.com>

CAUTION

Фирма *МикроЛАБ Системс Лтд (МЛС)* оставляет за собой право вносить любые изменения и прекращать выпуск и поддержку любых изделий и программного обеспечения, упоминаемых в настоящем документе, без какого-либо предварительного уведомления, если иное специально не оговаривается. *МЛС* рекомендует своим покупателям пользоваться подлинными и самыми последними версиями фирменных информационных документов и осуществлять предварительное консультирование с фирмой перед размещением заказа, чтобы быть уверенным, что настоящая информация достоверна и применима на текущий момент.

МЛС гарантирует качество и соответствие технических параметров поставляемой продукции приведенной технической спецификации. Всякое тестирование и проверка продукции производятся фирмой в степени и объемах, необходимых для поддержки настоящей гарантии. Какое-либо дополнительное тестирование и проверка продукции на соответствие другим требованиям проводятся лишь и только в случаях, выполняемых по специальным заказам, или тогда, когда это специально оговаривается.

МЛС не несет никакой ответственности за правильность функционирования и работоспособность оборудования и программного обеспечения, разработанного и изготовленного с применением продукции (или отдельных ее компонентов) фирмы, если это не подтверждено специальным фирменным сертификатом *МЛС*.

Продукция *МЛС* не предназначена для применения в аппаратуре, системах или изделиях для поддержки жизнедеятельности. Применение продукции *МЛС* в таком оборудовании категорически запрещено без специального письменного подтверждения от *МЛС* или оригинального фирменного сертификата *МЛС*.

IMPORTANT NOTICE

Настоящая продукция предназначена для использования в составе лабораторного тестового и научно-исследовательского оборудования. *МЛС* не несет ответственности за работоспособность настоящей продукции в составе другого типа оборудования и/или в отличных от специфицированных условиях эксплуатации. При повреждениях настоящей продукции, вызванных ее применением в составе другого типа оборудования и/или условий эксплуатации, гарантийные обязательства аннулируются без какого-либо возмещения ущерба и ремонт производится за счет покупателя.

Настоящая продукция генерирует, использует и может излучать радиочастотную энергию, которая может создавать радиочастотные помехи для другой аппаратуры, несмотря на все конструктивные и другие меры, предпринятые для минимизации создаваемых помех. Однако, в случае возникновения помех для работы другой аппаратуры покупатель должен сам и за свой счет принять меры для их устранения или уменьшения.

ITEMS OF LICENSE AGREEMENT

Никакие части настоящего документа, аппаратные и программные части настоящей продукции не могут быть реассемблированы, ретрассированы и/или изменены с целью восстановления и/или изменения электрической схемы, конструкции, алгоритма работы или принципа функционирования любыми методами, воспроизведены, скопированы, запомнены в архивах с возможностью воспроизведения, а также переданы по средствам связи в любом виде и любыми методами, будь то электронные, механические, копировальные, фотографические, записывающие или другие, без предварительно выданного фирменного письменного разрешения от *МЛС*. Нарушение настоящего положения вне зависимости от приобретения настоящей продукции и/или документа трактуется как нарушение авторских прав и преследуется по закону.

Приобретение настоящей продукции автоматически означает согласие покупателя с положениями лицензионного соглашения, равно как и другими положениями закона об авторских правах. Нарушение настоящих положений, равно как и других положений закона об авторских правах, трактуется как нарушение авторских прав, преследуется по закону и автоматически ведет к аннулированию всех обязательств *МЛС* по поддержке настоящей продукции.

Copyright © 1993-2002, MicroLAB Systems Ltd. All rights reserved.

About this Document

This user's guide contains description for *MIRAGE-P510D* universal dual-channel MPSD/JTAG emulator for TI TMS320 DSP for PCI-bus personal computers.

This document does not include detail description neither for TI DSP nor for the corresponding software and applications. Please refer to the following original documentation:

1. ***MIRAGE-P510D and UECMX Universal TMS320 DSP Emulators for ISA-bus PC User's Guide.*** MicroLAB Systems, 1999.
2. ***Code Composer C3x/C4x User's Guide.*** Texas Instruments Inc, USA, 1999
3. ***Code Composer Studio C5000 User's Guide.*** Texas Instruments Inc, USA, 2001
4. ***Code Composer Studio C6000 User's Guide.*** Texas Instruments Inc, USA, 2001

Warranty

The warranty period for all hardware and software products manufactured by MicroLAB Systems Ltd is *one year* after shipment. MicroLAB Systems Ltd guarantees free of charge repair or replacement for the manufacturer caused damaged products during warranty period. Software updates will be sent free of charge to the customer during warranty period.

Product registration procedure

MicroLAB Systems strongly recommends that you register each of your purchased hardware/software product in order to get free product updates and free technical support within the warranty period.

The registration procedure is as easy as the following:

- Open the PRODUCT REGISTRATION FORM, which is contained in the REGISTER.TXT text file available either on the MicroLAB Systems 'Technical & Programming Guide' CD-ROM or from the MicroLAB Systems FTP-site. If you are unable to locate the REGISTER.TXT file, then call/email to MicroLAB Systems.
- Fill in the applicable fields of the PRODUCT REGISTRATION FORM. It is important that you will to specify your name, post address, phone/fax, email address, purchased product name and serial number, and the product reception date.
- Return the PRODUCT REGISTRATION FORM to MicroLAB Systems either via email, fax or regular mail.

Note, that all product purchased from MicroLAB Systems shall be registered within 90 days after the date of the shipment.

If you need assistance, documentation or information...

Should you need technical assistance for purchased MicroLAB Systems Ltd products, or if you want to order additional documentation, or if you want to get latest information about MicroLAB Systems Ltd products, please email, call, fax or post to MicroLAB Systems Ltd customer support service:

<i>address:</i>	59a Beskudnikovsky blvd, 127486, Moscow, RUSSIA <i>MicroLAB Systems Ltd</i>
<i>phone/fax:</i>	+7-(095)-485-6332

information request: info@mlabsys.com
technical support: support@mlabsys.com
product registration: register@mlabsys.com
WWW: <http://www.mlabsys.com>
FTP: <ftp://ftp.mlabsys.com>

Trademarks

TORNADO-3x, TORNADO-4x, TORNADO-54x, TORNADO-P6x, TORNADO-P3x, TORNADO-PX, TORNADO-SX, TORNADO-E, MIRAGE-P510D, UECMX, MIRAGE-P510D, PIOX-Link are trademarks of *MicroLAB Systems Ltd*

TMS320, XDS510, Code Composer are trademarks of *Texas Instruments Inc*

Other trademarks and company names used are trademarks of their respective holders.

WINDOWS is a trademark of *Microsoft Corporation*

Other trademarks and company names used are trademarks of their respective holders.

Contents

Chapter 1. Introduction	1
1.1 General information	1
1.2 Host PC requirements	3
1.3 Technical specifications	3
Chapter 2. Construction	5
2.1 <i>MIRAGE-P510D</i> emulator and <i>MP510D/ECM</i> module	5
2.2 MP510D pod	8
2.3 JTAG pod	11
Chapter 3. Installation	15
3.1 Installation of <i>MP510D/ECM</i> emulator expansion DCM onto <i>MIRAGE-P510D</i> mainboard	15
3.2 Connection of MP510D/JTAG pod to <i>MIRAGE-P510D</i> emulator and <i>MP510D/ECM</i> emulator expansion mainboard	16
Chapter 4. Utility Software	17
4.1 Utility software	17
4.2 Configuring TI Code Composer debug tools for running with <i>MIRAGE-P510D</i> emulator	18

Figures

<i>Fig.1-1. MIRAGE-P510D dual-channel emulator with MP510D/ECM emulator expansion daughter-card module and MP510D and JTAG pods.</i>	1
<i>Fig.2-1. MIRAGE-P510D emulator mainboard.</i>	6
<i>Fig.2-2. Emulation control of target TMS320 DSP via on-board emulation controller of MIRAGE-P510D emulator mainboard.</i>	6
<i>Fig.2-3. MP510D/ECM optional emulator expansion DCM for MIRAGE-P510D emulator.</i>	7
<i>Fig.2-4. Emulation control of target TMS320 DSP via on-board emulation controller of MP510D/ECM emulator expansion DCM.</i>	8
<i>Fig.2-5. MP510D pod.</i>	9
<i>Fig.2-6. Pinout of male header for attachment of MP510D pod to scan-path emulation interface of target TMS320C3x DSP (top view).</i>	10
<i>Fig.2-7. JTAG pod.</i>	11
<i>Fig.2-8. Pinout of male header for connection of JTAG pod to scan-path emulation interface of target TMS320 DSP (top view).</i>	12
<i>Fig.3-1. Installation of MP510D/ECM emulator expansion DCM onto MIRAGE-P510D mainboard.</i>	15

Tables

<i>Table 2-2.</i> Setting resistor terminators for <i>TDO</i> and <i>TCK_RET</i> JTAG signals in JTAG pod.	12
<i>Table 2-3.</i> Setting active edge of <i>TCK_RET</i> clock for clocking <i>TMS</i> and <i>TDI</i> JTAG signals in JTAG pod.	13

Chapter 1. Introduction

This chapter contains general description for *MIRAGE-P510D* universal dual-channel MPSD/JTAG emulator for TI TMS320 DSP for PCI-bus personal computers.

1.1 General information

MIRAGE-P510D universal dual-channel MPSD/JTAG emulator (fig.1-1) has been designed for emulation control of TI TMS320 DSP.



Fig.1-1. *MIRAGE-P510D* dual-channel emulator with *MP510D/ECM* emulator expansion daughter-card module and MPSD and JTAG pods.

General construction

MIRAGE-P510D emulator installs into PCI-bus slot of host PC and comes either in one- or dual-channel configuration.

Each channel provides universal MPSD/JTAG emulation control for target TI TMS320 DSP. The *MIRAGE-P510D* emulator PCI-us plug-in mainboard itself includes one universal MPSD/JTAG emulation controller and expansion site for optional *MP510D/ECM* emulator expansion daughter-card module (DCM).

External MPSD or JTAG pods are used to connect *MIRAGE-P510D* and *MP510D/ECM* on-board emulation controller to target either MPSD or JTAG DSP on-chip emulation scan-path interface.

Supported DSP

MIRAGE-P510D universal dual-channel MPSPD/JTAG emulator supports TI TMS320C30/C31/C32 DSP with on-chip MPSPD emulation scan-path interface and TI TMS320VC33, TMS320C5xxx and TMS320C6xxx DSP with on-chip JTAG emulation scan-path interface.

CAUTION

Check with MicroLAB Systems for emulation support of other TI TMS320 DSP and mixed-platforms CPU using *MIRAGE-P510D* PCI-bus plug-in universal dual-channel MPSPD/JTAG emulator.

General features

MIRAGE-P510D emulator offers a powerful set of features for development and debugging of TI TMS320 DSP based hardware and software:

- supports both TI MPSPD (TMS320C3x) and TI JTAG (TMS320VC33//C5xxx/C6xxx and more coming...) scan-path interfaces
- provides up to two independent emulation channels when *MP510D/ECM* emulator expansion DCM is installed onto *MIRAGE-P510D* PCI-bus plug-in mainboard
- supports multiple devices in a single JTAG path
- includes 32-bit PCI-bus interface
- supported by power TI Code Composer and Code Composer Studio IDE debugging tools
- target TMS320 DSP emulation features:
 - reads/writes to the DSP on-chip registers and I/O ports
 - provides access to the DSP on/off-chip memory, performs program/data upload and download
 - supports software/hardware breakpoints
 - supports program profiling and execution time measurement
 - signal graphics
 - file I/O
 - many more ...
- MPSPD pod provides optional target TMS320C3x DSP RESET control for reliable emulation
- MPSPD pod provides optional LED indicators for target TMS320C3x DSP chip POWER, CLOCK and RESET signals
- JTAG pod provides optional LED indicators for target DSP chip POWER and JTAG *TCK* and *TRST* signals
- MPSPD and JTAG pods provide compatibility with all 3v/5v target TMS320 DSP
- MPSPD and JTAG pods for *MIRAGE-P510D* emulator are compatible with those for MicroLAB Systems *UECMX*, *MIRAGE-510DX*, *MIRAGE-510D*, *MIRAGE-30D* scan-path emulators and connect to scan-path interface of target TMS320 DSP via interface headers, which are compatible with the corresponding headers for TI XDS510 scan-path emulator
- many more ...

Software development tools

MIRAGE-P510D emulator runs under the industry standard TI Code Composer and Composer Studio IDE debugging tools for Windows 95/98 and Windows NT/2000. All debuggers support debugging of target DSP software both in C and Assembly source codes.

Software development is supported by the corresponding TI Floating-Point or Fixed-Point DSP Optimizing C Compilers and Assembly Language Tools.

1.2 Host PC requirements

The following are minimum host PC requirements that should be matched for normal operation of MIRAGE-P510D emulator and TI Code Composer and Composer Studio IDE tools:

- host PC with Pentium CPU (Pentium III running at 500MHz or higher is recommended) and at-least one 32-bit PCI-bus slot for installation of MIRAGE-P510D emulator
- Windows 95/98/NT/2000 installed
- 32Mbyte of RAM (128Mbyte is recommended)
- CD-ROM drive for software installation
- at least 300 MB of free hard disk space
- SVGA or higher adapter (XGA is recommended)

1.3 Technical specifications

The following are technical specifications for MIRAGE-P510D emulator for the environment temperature +25°C.

<u>Parameter description</u>	<u>parameter value</u>
MIRAGE-P510D host PC interface	33MHz 32-bit PCI-bus
number of on-board MPSD/JTAG emulation control channels	1
number of sites for optional MP510D/ECM emulator expansion DCM	1
MIRAGE-P510D emulator power consumption (with two pods and MP510D/ECM DCM installed)	+5v@0.85A
dimensions of MIRAGE-P510D emulator mainboard	89x57 mm (3.5"x2.25") (half-size PCI-board)
temperature range	0..+50°C
external MPSD and JTAG pods:	
output high level with the load current I_{OH} =48ma at all outputs	≥2v, TTL 3v compatible
output low level with the load current I_{OH} =48ma at all outputs	≤0.5v

input high level at all inputs	≥2v, TTL 5v compatible
input low level at all inputs	≤0.5v
length of connection cable between pod and UECMX	≥1m
length of connection cable for connection to scan-path interface of target DSP	≥0.1m
JTAG and MPSD pod dimensions	89x57x25 mm

Chapter 2. Construction

This chapter contains information about construction for *MIRAGE-P510D* emulator and for MP510D and JTAG pods.

2.1 *MIRAGE-P510D* emulator and *MP510D/ECM* module

MIRAGE-P510D universal dual-channel MP510D/JTAG emulator for TI TMS320 DSP comprises of the following components:

- *MIRAGE-P510D* emulator PCI-bus plug-in mainboard
- optional *MP510D/ECM* emulator expansion daughter-card module (DCM)
- one or two MP510D or JTAG pods.

MIRAGE-P510D emulator can come in either single channel or dual-channel configuration with either one or two MP510D/JTAG pods correspondingly.

CAUTION

MIRAGE-P510D emulator is PCI-bus plug-in peripheral device and complies with Plug and Play PCI-bus requirements.

There is no configuration jumpers and switches neither on *MIRAGE-P510D* emulator mainboard, nor on the *MP510D/ECM* emulator expansion DCM.

MIRAGE-P510D emulator configuration setting and control are performed via host PC software.

MIRAGE-P510D mainboard

MIRAGE-P510D emulator PCI-bus plug-in mainboard (fig.2-1) has been designed to plug into any 32-bit PCI-bus slot of host PC and includes 32-bit 33MHz host PCI-bus interface, one universal MP510D/JTAG emulation control channel, and on-board expansion site for optional *MP510D/ECM* emulator expansion DCM.




Fig.2-1. *MIRAGE-P510D* emulator mainboard.

On-board universal MP510D/JTAG emulation controller of *MIRAGE-P510D* emulator mainboard provides emulation control of target TMS320 DSP (fig.2-2) with either MP510D (TMS320C3x, TMS320C5xxx, TMS320C6xxx, etc) DSP on-chip scan-path emulation interface via external MP510D or JTAG pod correspondingly (see corresponding section below in this chapter for detail information about JTAG and MP510D pods), which connects to *MIRAGE-P510D* emulator on-board JP1 connector (refer to fig.1-1 and fig.2-2). This comes as standard single-channel configuration of *MIRAGE-P510D* emulator.




Fig.2-2. Emulation control of target TMS320 DSP via on-board emulation controller of *MIRAGE-P510D* emulator mainboard.

Optional *MP510D/ECM* emulator expansion DCM with second MP510D or JTAG pod are used in case dual-channel configuration of *MIRAGE-P510D* emulator is required. *MP510D/ECM* emulator expansion DCM plugs into on-board JP2 expansion site of *MIRAGE-P510D* emulator mainboard and second MP510D or JTAG pod is connected directly to *MP510D/ECM* emulator expansion DCM.

MP510D/ECM emulator expansion DCM

MP510D/ECM emulator expansion DCM (fig.2-3) must be used for dual-channel expansion of *MP510D/ECM* emulator mainboard.




Fig.2-3. MP510D/ECM optional emulator expansion DCM for MIRAGE-P510D emulator.

MP510D/ECM emulator expansion DCM plugs into on-board JP2 expansion site of *MIRAGE-P510D* emulator mainboard. On-board universal MPSD/JTAG emulation controller of *MP510D/ECM* emulator expansion DCM provides emulation control of target TMS320 DSP (fig.2-4) with either MPSD or JTAG DSP on-chip scan-path emulation interface via external MPSD or JTAG pod correspondingly (see corresponding section below in this chapter for detail information about JTAG and MPSD pods), which connects to *MP510D/ECM* on-board JP1 connector (refer to fig.1-1 and fig.2-4). This comes as standard single-channel configuration of *MIRAGE-P510D* emulator.




Fig.2-4. Emulation control of target TMS320 DSP via on-board emulation controller of MP510D/ECM emulator expansion DCM.

MPSD and JTAG pods

MPSD and JTAG pods, which are used for connection of on-board emulation controllers of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM to external TI TMS320 DSP.

MPSD and JTAG pods used with *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM are the same pods, which have been used with *MIRAGE-510DX*, *MIRAGE-510D* and *MIRAGE-30D* dual-channel emulators for ISA-bus and *UECMX*, *UECM-30*, and *UECM* universal emulator DCM for *TORNADO* DSP systems from MicroLAB Systems. Both MPSD and JTAG pods provide compatibility with all 3v/5v target TMS320 DSP.

MPSD pod is used for emulation of external TMS320C3x (TMS320C30/C31/C32) DSP only. MPSD pod is connected to target TMS320C3x DSP via user supplied 12-pin male header that is compatible with that for TI XSD510 emulator.

JTAG pod is used for emulation of external TMS320C2xx/VC33/C4x/C5x/C54x/C6x/C8x DSP. JTAG pod is connected to target TMS320 DSP via user supplied 14-pin male header that is compatible with that for TI XSD510 emulator.

2.2 MPSD pod

MPSD pod (fig.2-5) is designed for connection between on-board emulation controller of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM and scan-path interface of external target TMS320C3x (TMS320C30/C31/C32) DSP only.



Fig.2-5. MPSP pod.

CAUTION

No other TMS320 DSP except for TMS320C3x (TMS320C30/C31/C32) DSP allow connection of MPSP pod to DSP on-chip MPSP scan-path emulation interface.

Connection of MPSP pod to on-board emulation controllers of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM

MPSP pod connects to on-board emulation controllers of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM via the 20-pin connector at the end of the pod's shielded cable via the mounting bracket of *MIRAGE-P510D* mainboard. It plugs into JP1 on-board connector of *MIRAGE-P510D* emulator mainboard (fig.2-2) or into JP1 on-board connector of *MP510D/ECM* emulator expansion DCM (fig.2-4).

Connection of MPSP pod to scan-path interface of target TMS320C3x DSP

MPSP pod connects to scan-path emulation interface of target TMS320C3x DSP via 12-pin dual-row male header, which should be provided on the target TMS320C3x DSP based equipment and should be compatible with that for connection of TI XDS510 scan-path emulator. Scan-path signals specifications are identical to those for TI XDS510 scan-path emulator. MPSP pod provides compatibility with all 3v/5v target TMS320C3x DSP.

Fig. 2-6 shows pinout of the MPSP 12-pin male header for target TMS320C3x DSP based equipment for connection to MPSP pod.




Fig.2-6. Pinout of male header for attachment of MPSD pod to scan-path emulation interface of target TMS320C3x DSP (top view).

For more information about MPSD scan-path emulation interface signals of TMS320C3x DSP refer to original technical documentation from TI.

RESET signal control for target TMS320C3x DSP

MPSD pod provides optional facility for remote control of RESET signal for target TMS320C3x DSP chip. This has approved to increase reliability of scan-path emulation control of target TMS320C3x DSP chip.

CAUTION

MPSD pod supports generation of RESET signal for target TMS320C3x DSP only.

MPSD pod provides 2-pin female connector (see fig.2-6) that includes two reset signals of opposite polarities (*RESET* and *RESET*), which might be connected to the target TMS320C3x DSP hardware in order to provide control of target TMS320C3x DSP reset signal.

CAUTION

MPSD pod generates target TMS320C3x DSP reset signal of opposite polarities (*RESET* and *RESET*).

Actual selection of target DSP RESET signal polarity should be done by user in accordance with schematics of target hardware.

RESET and *RESET* outputs of MPSD pod provide the load current 48 ma for both high and low output 3v/5v TTL compatible signal levels.

Indication of target TMS320C3x DSP status

For user convenience, MPSD pod provides LED indicators for the following signals:

- 'ACTIVE' LED indicates activity of MPSD pod and is always on in case MPSD pod is connected to *MIRAGE-P510D* emulator mainboard or *MP510D/ECM* emulator expansion DCM.
- 'T-POWER' LED indicates validity of target TMS320C3x power supply. In case the 'T-POWER' LED has continuous green lighting, then the power is applied to target DSP. In case this LED blinks, then no power is applied to target DSP.
- 'T-CLOCK' LED indicates validity of target H3 output clock. When H3 target clock is absent or not connected to MPSD pod interface header, then no scan-path emulation control of target TMS320C3x DSP chip is available.
- 'T-RESET' LED indicates activity of optional target RESET signal generated by emulation controller of *MIRAGE-P510D* emulator mainboard or *MP510D/ECM* emulator expansion DCM.

2.3 JTAG pod

JTAG pod (fig.2-5) is designed for connection between on-board emulation controller of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM and scan-path interface of external target TMS320 DSP with JTAG scan-path emulation interface (TMS320C2xx/VC33/C4x/C5x/C54x/C6x/C8x).



Fig.2-7. JTAG pod.

CAUTION

No other TMS320 DSP except for TMS320 DSP with on-chip JTAG scan-path emulation interface allow connection of JTAG pod to DSP on-chip JTAG scan-path emulation interface.

Connection of JTAG pod to on-board emulation controllers of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM

JTAG pod connects to on-board emulation controllers of *MIRAGE-P510D* emulator mainboard and *MP510D/ECM* emulator expansion DCM via the 20-pin connector at the end of the pod's shielded cable via the mounting bracket of *MIRAGE-P510D* mainboard. It plugs into JP1 on-board connector of *MIRAGE-P510D*

emulator mainboard (fig.2-2) or into JP1 on-board connector of *MP510D/ECM* emulator expansion DCM (fig.2-4).

Connection of JTAG pod to scan-path interface of target TMS320 DSP

JTAG pod connects to scan-path emulation interface of target TMS320 DSP via 14-pin dual-row male header, which should be provided on the target TMS320 DSP based equipment and should be compatible with that for connection of TI XDS510 scan-path emulator. Scan-path signals specifications are identical to those for TI XDS510 scan-path emulator. JTAG pod provides compatibility with all 3v/5v target TMS320 DSP.

Fig. 2-8 specifies pinout of the JTAG 14-pin male header for target TMS320 DSP based equipment for connection to JTAG pod.




Fig.2-8. Pinout of male header for connection of JTAG pod to scan-path emulation interface of target TMS320 DSP (top view).

For more information about JTAG scan-path emulation interface signals of TMS320 DSP refer to original technical documentation from TI.

Setting terminators for TDO and TCK_RET JTAG signals

JTAG pod provides optional facility for setting 220/270 Ohm parallel resistor terminators for *TDO* and *TCK_RET* JTAG scan-path signals. This delivers noise reduction and increase reliability of JTAG operation, however this requires high-current output drivers in the target hardware, and might be not applicable for all designs. To get more information about signal terminators for *TDO* and *TCK_RET* JTAG signals refer to section "*XDS510 Emulator Design Considerations*" of the corresponding TI TMS320 User's Guide.

In order to set terminators for *TDO* and *TCK_RET* JTAG signals you have to use buttons #3 and #4 of DIP-switch, which is located at the bottom of JTAG pod.

Table 2-2. Setting resistor terminators for *TDO* and *TCK_RET* JTAG signals in JTAG pod.

DIP-switch of JTAG pod	state of the button	description
button #4	OFF	resistor terminator 220/270 Ohm for signal <i>TDO</i> is off
	ON	resistor terminator 220/270 Ohm for signal <i>TDO</i> is on
button #3	OFF	resistor terminator 220/270 Ohm for signal <i>TCK_RET</i> is off
	ON	resistor terminator 220/270 Ohm for signal <i>TCK_RET</i> is on

Notes: The highlighted configurations correspond to default factory settings.

Setting active edge of *TCK_RET* clock signal for clocking *TMS* and *TDI* JTAG signals

JTAG pod provides optional facility for setting active edge of *TCK_RET* clock signal that is used for clocking *TMS* and *TDI* JTAG scan-path signals. This facility allows to increase clocking frequency of JTAG path and increase its performance. Default clocking edge is the rising edge of *TCK_RET* clock. To get more information about clocking of *TMS* and *TDI* JTAG signals refer to section “*XDS510 Emulator Design Considerations*” from the corresponding TI TMS320 User’s Guide.

In order to set active edge of *TCK_RET* clock signal for clocking *TMS* and *TDI* JTAG signals you have to use buttons #1 and #2 of DIP-switch, which is located at the bottom of JTAG pod.

Table 2-3. Setting active edge of *TCK_RET* clock for clocking *TMS* and *TDI* JTAG signals in JTAG pod.

Button #1 of DIP-switch in JTAG pod	button #2 of DIP-switch in JTAG pod	description
OFF	OFF	Reserved (do not use)
OFF	ON	Rising edge of <i>TCK_RET</i> is used to clock <i>TMS</i> and <i>TDI</i> signals. This configuration should be set when <i>UECMX</i> is configured for TI XDS510 emulation compatibility mode.
ON	OFF	Falling edge of <i>TCK_RET</i> is used to clock <i>TMS</i> and <i>TDI</i> signals.
ON	ON	Reserved (do not use)

Notes: The highlighted configuration corresponds to the factory settings.

Indication of target DSP status

For user convenience, JTAG pod includes LED indicators for the following signals:

- **'ACTIVE'** LED indicates activity of MPSD pod and is always on in case JTAG pod is connected to *MIRAGE-P510D* emulator mainboard or *MP510D/ECM* emulator expansion DCM.
- **'T-POWER'** LED indicates validity of target DSP power supply. In case **'T-POWER'** LED has continuous green lighting, then the power is applied to target DSP. In case this LED blinks, then no power is applied to target DSP.
- **'TCK_RET'** LED indicates validity of JTAG path clock. When JTAG return path clock is absent or not returned back to JTAG pod interface header, then no scan-path emulation control of target DSP is available.
- **'TRST'** LED indicates activity of JTAG path RESET signal generated by emulation controller of *MIRAGE-P510D* emulator mainboard or *MP510D/ECM* emulator expansion DCM.

Chapter 3. Installation

This chapter contains instructions for installation of *MIRAGE-P510D* emulator and how to connect *MIRAGE-P510D* emulator and *MP510D/ECM* emulator expansion DCM to target TMS320 DSP.

3.1 Installation of *MP510D/ECM* emulator expansion DCM onto *MIRAGE-P510D* mainboard

MP510D/ECM emulator expansion DCM must be installed onto *MIRAGE-P510D* emulator mainboard in case dual-channel configuration of *MIRAGE-P510D* emulator is required.

MP510D/ECM emulator expansion DCM installs into on-board JP2 expansion connector site of *MIRAGE-P510D* emulator mainboard (refer to fig.2-1). Figure 3-1 demonstrates installation of *MP510D/ECM* emulator expansion DCM must be installed onto *MIRAGE-P510D* emulator mainboard.

The following are general guides for installation of *MP510D/ECM* emulator expansion DCM must be installed onto *MIRAGE-P510D* emulator mainboard:

- slant *MP510D/ECM* emulator expansion DCM
- insert *MP510D/ECM* emulator expansion DCM on-board connector JP1 for connection to external pod into the corresponding hole at *MIRAGE-P510D* mounting bracket
- plug in *MP510D/ECM* emulator expansion DCM male header into the JP2 expansion female connector site on *MIRAGE-P510D* mainboard
- screw-in the *MP510D/ECM* emulator expansion DCM to the *MIRAGE-P510D* mainboard using two supplied screws.




Fig.3-1. Installation of *MP510D/ECM* emulator expansion DCM onto *MIRAGE-P510D* mainboard.

3.2 Connection of MPSD/JTAG pod to *MIRAGE-P510D* emulator and *MP510D/ECM* emulator expansion mainboard

The following are general guides for connection of MPSD or JTAG pod to JP1 on-board connector of *MIRAGE-P510D* emulator mainboard or JP1 on-board connector of *MP510D/ECM* emulator expansion DCM:

- switch off power of host PC where *MIRAGE-P510D* emulator mainboard is installed
- install *MIRAGE-P510D* emulator mainboard into PCI-bus slot of host PC and screw-in the mounting bracket of *MIRAGE-P510D* emulator mainboard to the rear panel of host PC
- insert the 20-pin on-cable connector of MPSD or JTAG pod into the corresponding pod plug-in connector of either *MIRAGE-P510D* emulator mainboard or *MP510D/ECM* emulator expansion DCM and ensure that it has been fixed by hearing the typical sound click
- switch on power of host PC
- Connect MPSD or JTAG pod to scan-path interface of target TMS320 DSP.

Chapter 4. Utility Software

This chapter contains information about utility software for *MIRAGE-P510D* emulator and how to configure TI Code Composer Studio debug tools in order to run with *MIRAGE-P510D* emulator hardware.

4.1 Utility software

MIRAGE-P510D emulator has been designed to run under TI Code Composer and Code Composer Studio debug tools, so its control is performed completely automatically via the corresponding software drivers for TI Code Composer and Code Composer Studio.

CAUTION

MIRAGE-P510D emulator is PCI-bus plug-in peripheral device and complies with Plug and Play PCI-bus requirements.

There is no user configurable parameters and control settings for *MIRAGE-P510D* emulator.

The only utility software provided for *MIRAGE-P510D* emulator is the *MP510D_LIST.EXE MIRAGE-P510D* emulator list utility, which must be used to view a list and configuration of installed *MIRAGE-P510D* emulators and to obtain logical ID for each of available emulation control channels. Emulation channel ID is required in order to configure TI Code Composer configuration tools to run with this emulation channel.

Installation of utility software

In order to install utility software for *MIRAGE-P510D* emulator, follow instructions provided in the utility software installation directory on MicroLAB Systems CD. Utility software for *MIRAGE-P510D* emulator runs under Windows 9x, Windows NT and Windows 2000.

Running utility software

MP510D_LIST.EXE MIRAGE-P510D emulator list utility has been designed to be invoked from command line prompt window of Windows:

MP510D_LIST

Provided display output contains list for all detected *MIRAGE-P510D* emulator and available emulator channels. Emulator channel ID, external pod configuration, power loss detector and is provided for each available emulator channel, as well as the PCI-bus number and PCI-bus slot numbers are provided for each detected *MIRAGE-P510D* emulator.

Emulator channel ID

Utility software and TI Code Composer Studio debug tools are using logical emulator channel ID in order to address particular *MIRAGE-P510D* emulator channel from all detected in host PC.

The following are general rules for how emulator channel ID is being processed by utility software and TI Code Composer debug tools:

- Emulation channel ID are numbered starting from the '0' value.
- Two succeeding emulator channel ID are reserved for each *MIRAGE-P510D* emulator. The even value is used for identifying on-board emulation channel of *MIRAGE-P510D* emulator mainboard. The odd value is reserved for identifying on-board emulation channel of *MP510D/ECM* emulator expansion DCM, which comes valid only in case *MP510D/ECM* emulator expansion DCM is installed.
- Emulation channel ID equal to the '0' value is assigned to on-board emulation channel of *MIRAGE-P510D* emulator mainboard, which is installed into the PCI-bus slot with the lowest number. Note, that PCI-bus slots are typically numbered from left to right if looking from the front panel of opened host PC compartment.

4.2 Configuring TI Code Composer debug tools for running with *MIRAGE-P510D* emulator

MIRAGE-P510D emulator has been designed to run under TI Code Composer and Code Composer Studio debug tools using compatible driver provided by MicroLAB Systems.

CAUTION

MIRAGE-P510D emulator driver for TI C5xxx/C6xxx Code Composer Studio debug tools runs with Code Composer Studio version 2.0 and later.

Installation of *MIRAGE-P510D* driver for TI Code Composer and Composer Studio debug tools

In order to install *MIRAGE-P510D* compatible driver for TI Code Composer and Composer Studio debug tools, follow instructions provided in the Code Composer driver installation directory on MicroLAB Systems CD. *MIRAGE-P510D* compatible driver for TI Code Composer and Composer Studio debug tools runs under Windows 9x, Windows NT and Windows 2000.

Configuring TI Code Composer and Code Composer Studio debug tools to run with *MIRAGE-P510D* hardware

TI Code Composer and Code Composer Studio debug tools are using the corresponding Code Composer configuration tool (*CC_SETUP.EXE* utility) in order to select the emulator, which will be used to run Code Composer or Code Composer Studio debug tools.

The following are general rules for how to configure Code Composer and Code Composer Studio debug tools to run with *MIRAGE-P510D* hardware via Code Composer configuration tool (*CC_SETUP.EXE*):

-
- Run *MP510D_LIST.EXE* *MIRAGE-P510D* emulator list utility (refer to section 4.1) and obtain emulation channel ID for particular emulator channel, which will be used to run Code Composer and Code Composer Studio IDE.
 - Run *CC_SETUP.EXE* Code Composer configuration tool and follow instructions provided with the installed *MIRAGE-P510D* compatible driver in the Code Composer driver installation directory on MicroLAB Systems CD.